

## Hydraulic breaker Model SP-750

| Specification                     | Unit/Model         | SP-750    |
|-----------------------------------|--------------------|-----------|
| Total weight (boxed silent model) | kg                 | 375       |
| Length                            | mm                 | 1860      |
| Hydraulic oil pressure            | kg/cm <sup>2</sup> | 120-150   |
|                                   | psi                | 1680-2100 |
|                                   | bar                | 117-147   |
| Hydraulic oil flow                | l/min              | 50-90     |
| Impact frequency                  | bpm                | 400-800   |
| Hose diameter                     | mm                 | 12.7      |
|                                   | inch               | 0.5       |
| Chisel diameter                   | mm                 | 75        |
| Chisel weight                     | kg                 | 23        |
| Applicable machine weight         | ton                | 6-9       |
| Impact power                      | ft-lbs             | 663       |
|                                   | Joule              | 900       |
| Main valve type                   |                    | Inward    |
| Accumulator                       |                    | No        |
| Accumulator pressure              | kg/cm <sup>2</sup> | N/A       |
| Nitrogen pressure                 | kg/cm <sup>2</sup> | 16.5      |



SEEMARK (AUSTRALIA) PTY LTD  
 2785 Remembrance Drive, Tahmoor NSW 2573  
 0408 219 212  
[www.seemark.com.au](http://www.seemark.com.au)